

CHAIN & SPROCKETS



CHAIN

Chain Pitch	Rating	Type	Other info	Net Price £	Availability (Stock)	Quantity
2" (50.8mm)	6,000lbs	Hollow Bearing Pin	1.25" (31.75mm) Dia. Roller	2.50	Stock	sold
CL		Clip Type		0.61	Stock	16
3" (76.2mm)	6,000lbs	Hollow Bearing Pin	1.25" (31.75mm) Dia. Roller	2.14	Stock	200
CL		Clip Type		0.81	Stock	20
6" (152.4mm)	6,000lbs	Hollow Bearing Pin	1.25" (31.75mm) Dia. Roller	1.62	Stock	200
CL		Clip Type		1.32	Stock	20
4" (101.6mm)	12,000lbs	Hollow Bearing Pin	1.875" (47.625mm) Dia. Roller	4.20	Stock	200
CL		Clip Type		2.07	Stock	20
6" (152.4mm)	24,000lbs	Hollow Bearing Pin	2.625" (66.675mm) Dia. Roller	7.53	Stock	200
CL		Clip Type		5.94	Stock	20
2" (50.8mm)	7,500lbs	Solid Bearing Pin	1.25" (31.75mm) Dia. Roller	2.45	Stock	200
CL		Rivet Type		0.60	Stock	20
CL		Nut Type		0.66	Stock	20
3" (76.2mm)	7,500lbs	Solid Bearing Pin	1.25" (31.75mm) Dia. Roller	2.00	Stock	200
CL		Rivet Type		0.76	Stock	20
CL		Nut Type		0.83	Stock	20
4" (101.6mm)	7,500lbs	Solid Bearing Pin	1.25" (31.75mm) Dia. Roller	1.75	Stock	200
CL		Rivet Type		0.87	Stock	20
CL		Nut Type		0.94	Stock	20
4" (101.6mm)	15,000lbs	Solid Bearing Pin	1.875" (47.625mm) Dia. Roller	4.03	Stock	150
CL		Rivet Type		1.98	Stock	10
CL		Nut Type		2.18	Stock	20
4" (101.6mm)	15,000lbs	Solid Bearing Pin	K3-01	6.46	Stock	200
CL		Rivet Type		3.17	Stock	20
CL		Nut Type		3.49	Stock	20
6" (152.4mm)	15,000lbs	Solid Bearing Pin	1.875" (47.625mm) Dia. Roller	3.29	Stock	200
CL		Rivet Type		2.70	Stock	20
CL		Nut Type		2.96	Stock	20
2" (50.8mm)	7,500lbs	Solid Bearing Pin - Deep Link Sideplate	1.25" (31.75mm) Dia. Roller	3.33	Stock	200
CL		Rivet Type		0.82	Stock	20
CL		Nut Type		0.90	Stock	20
4" (101.6mm)	15,000lbs	Solid Bearing Pin - Deep Link Sideplate	1.875" (47.625mm) Dia. Roller	4.94	Stock	200
CL		Rivet Type		2.43	Stock	20
CL		Nut Type		2.68	Stock	20

SPROCKETS

Pitch	Rating	No. of Teeth	Net Price Each £	Availability (Stock)	Quantity
				(6/8 weeks)	
1.5" (38.1mm)	4,500lbs	8	5.34	stock	10
1.5" (38.1mm)	4,500lbs	12	9.14		
2" (50.8mm)	6,000lbs	8	11.14		
2" (50.8mm)	6,000lbs	10	14.23		
2" (50.8mm)	6,000lbs	12	17.97	stock	10
2" (50.8mm)	6,000lbs	14	25.74		
2" (50.8mm)	6,000lbs	16	32.31		
2" (50.8mm)	7,500lbs	8	11.14	stock	6
2" (50.8mm)	7,500lbs	10	14.23		
2" (50.8mm)	7,500lbs	12	17.97		
2" (50.8mm)	7,500lbs	14	25.74		
2" (50.8mm)	7,500lbs	16	32.31		
2.5" (63.5mm)	6,000lbs	8	14.73		
2.5" (63.5mm)	6,000lbs	12	26.12		
2.5" (63.5mm)	7,500lbs	8	14.73		
2.5" (63.5mm)	7,500lbs	12	26.12		
3" (76.2mm)	6,000lbs	8	19.36		
3" (76.2mm)	6,000lbs	10	27.55		
3" (76.2mm)	6,000lbs	12	31.58		
3" (76.2mm)	6,000lbs	16	40.37		
3" (76.2mm)	7,500lbs	8	19.36	stock	10
3" (76.2mm)	7,500lbs	10	27.55		
3" (76.2mm)	7,500lbs	12	31.58		
3" (76.2mm)	7,500lbs	16	40.37		
4" (101.6mm)	6,000lbs	8	28.48		
4" (101.6mm)	6,000lbs	10	34.18		
4" (101.6mm)	6,000lbs	12	40.56		
4" (101.6mm)	6,000lbs	16	57.28		
4" (101.6mm)	7,500lbs	8	28.48	stock	10
4" (101.6mm)	7,500lbs	10	34.18		
4" (101.6mm)	7,500lbs	12	40.56		
4" (101.6mm)	7,500lbs	16	57.28		